Application No.: 10/573,656 Docket No.: 0599-0214PUS1

AMENDMENTS TO THE CLAIMS

- 1. (Canceled)
- 2. (Canceled)
- 3. (Original) An adhesive resin composition for titanium or a titanium alloy, comprising: a thermosetting resin and an imidazole compound.
- 4. (Original) The adhesive resin composition for titanium or a titanium alloy according to claim 3, further comprising a thermoplastic resin.
- 5. (Previously Presented) The adhesive resin composition for titanium or a titanium alloy according to claim 3, wherein the imidazole compound is an imidazole silane compound.
 - 6. (Canceled)
- 7. (Previously Presented) The adhesive resin composition for titanium or a titanium alloy according to claim 4, wherein the thermoplastic resin has a fracture energy release rate G_{IC} of 4500J/m^2 or more.
- 8. (Currently Amended) The adhesive resin composition for titanium or a titanium alloy according to claim 4, wherein the <u>thermosetting</u> thermoplastic resin in the adhesive resin composition that has been cured is in a discontinuous phase as well as in a cohesive phase.
- 9. (Previously Presented) The adhesive resin composition for titanium or a titanium alloy according to claim 4, wherein the thermoplastic resin in the adhesive resin composition is a crystalline thermoplastic resin.
- 10. (Previously Presented) The adhesive resin composition for titanium or a titanium alloy according to claim 3, wherein the thermoplastic resin is an epoxy resin.

2

Application No.: 10/573,656 Docket No.: 0599-0214PUS1

11. (Previously Presented) An adhesive resin film for titanium or a titanium alloy comprising the adhesive resin composition according to claim 3.

- 12. (Previously Presented) A prepreg comprising the adhesive resin composition according to claim 3 and reinforcing fibers.
- 13. The prepreg according to claim 12, wherein the reinforcing fibers are impregnated with the adhesive resin composition.
- 14. (Original) The prepreg according to claim 12, wherein the adhesive resin composition is placed on a surface layer of the prepreg.
- 15. (Original) A prepreg comprising the adhesive resin film according to claim 11 placed on the surface layer of the prepreg.
- 16. (Previously Presented) The prepreg according to claim 12, wherein the reinforcing fibers are carbon fibers.
 - 17. (Canceled)
 - 18. (Canceled)
 - 19. (Canceled)
 - 20. (Canceled)
- 21. (Currently amended) A composite material wherein titanium or a titanium alloy and an adhere adhered are adhered to each other through an adhesive resin layer formed by curing the adhesive resin composition according to claim 3.
- 22. (Currently Amended) A composite material wherein titanium or a titanium alloy and an adhere adherend are adhered to each other through an adhesive resin layer formed by curing the adhesive resin film according to claim 11.

Application No.: 10/573,656 Docket No.: 0599-0214PUS1

23. (Currently Amended) The composite material according to claim 21, wherein the adhere adherend is a plastic material or a metal material.

- 24. (Currently Amended) The composite material according to claim 23, wherein the adhere adherend is a fiber-reinforced plastic.
- 25. (Previously Presented) A composite material wherein titanium or a titanium alloy and the prepreg according to claim 12 are adhered to each other.
- 26. (Currently Amended) The composite material according to claim 17, wherein the peel torque of the titanium or titanium alloy from the adhere adherend, measured in compliance with ASTM D 1781-98, is 5N-mm/mm or more.
 - 27. (Canceled)
 - 28 (Canceled)
 - 29. (Canceled)
 - 30. (Canceled)
- 31. (Original) A manufacturing method of a composite material comprising the steps of: applying an adhesive resin composition containing a thermosetting resin and a thermoplastic resin to the surface of titanium or a titanium alloy; and conducting a heating process to a temperature of not less than the melting point of the thermoplastic resin.